


Abrasive fibre disc

CS 565



Properties

Bonding agent	Resin
Grain	Zirconia alumina
Coating	Close

Application

Stainless steel	●
Steel	●
Metals	●

Product benefit

Self-sharpening effect - High aggressiveness on steel and stainless steel - Ideal for rough grinding work - Excellent price-performance ratio|Self-sharpening effect - High aggressiveness on steel and stainless steel - Ideal for rough grinding work - Excellent price-performance ratio - Special large package reduces storage costs

Available grits:

16 24 30 36 40 50 60 80 100 120 150 180 220 240 280 320 360 400 500 600 800 1000 1200 1500 2000 2500 3000										
Diameter x Hole in mm	Hole pattern	grain	Vmax m/s	Max. RPM	type of coat.abras.	bore shape	Packing unit/pcs.	Cat. number		
100 x 16	⊙ 10	24	80 m/s	15300 rpm	CS 565	round hole	25	100711		
100 x 16	⊙ 10	80	80 m/s	15300 rpm	CS 565	round hole	25	188678		
100 x 16	⊙ 10	36	80 m/s	15300 rpm	CS 565	round hole	25	23680		
100 x 16	⊙ 10	60	80 m/s	15300 rpm	CS 565	round hole	25	84604		

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany
 Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
 sales@klingspor.de - www.klingspor.de



Diameter x Hole in mm	Hole pattern	grain	Vmax m/s	Max. RPM	type of coat.abras.	bore shape	Packing unit/pcs.	Cat. number
115 x 22	⊗ 30	40	80 m/s	13300 rpm	CS 565	star shaped hole	25	242801
115 x 22	⊗ 30	36	80 m/s	13300 rpm	CS 565	star shaped hole	25	6686
115 x 22	⊗ 30	60	80 m/s	13300 rpm	CS 565	star shaped hole	25	6687
115 x 22	⊗ 30	80	80 m/s	13300 rpm	CS 565	star shaped hole	25	6688
115 x 22	⊗ 30	24	80 m/s	13300 rpm	CS 565	star shaped hole	25	95335
125 x 22	⊗ 30	80	80 m/s	12200 rpm	CS 565	star shaped hole	25	23005
125 x 22	⊗ 30	36	80 m/s	12200 rpm	CS 565	star shaped hole	25	6620
125 x 22	⊗ 30	60	80 m/s	12200 rpm	CS 565	star shaped hole	25	6721
125 x 22	⊗ 30	50	80 m/s	12200 rpm	CS 565	star shaped hole	25	93054
125 x 22	⊗ 30	24	80 m/s	12200 rpm	CS 565	star shaped hole	25	97643
180 x 22	⊗ 30	36	80 m/s	8500 rpm	CS 565	star shaped hole	25	65703
180 x 22	⊗ 30	60	80 m/s	8500 rpm	CS 565	star shaped hole	25	6690
180 x 22	⊗ 30	80	80 m/s	8500 rpm	CS 565	star shaped hole	25	6691
180 x 22	⊗ 30	24	80 m/s	8500 rpm	CS 565	star shaped hole	25	95993

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

