

Diamond cup grinding wheel

DS 600 B SUPRA



Properties

Design	Brazed
Segmentation	Standard
Aggression	■■■■■□□
Service life	■■■■■□□

Product benefit

Double row cup grinding wheel for machining concrete and abrasive materials - Efficient dust extraction - Aggressive grinding performance - Long service life - M14 adapter available, see DZ 114

Application

Concrete	●
Screed	●
Construction materials	●

Target group

- Building construction
- Floor tilers
- Concrete plants
- Natural stone businesses

Diameter x Bore in mm	Cup grinding wheel height [mm]	Vmax m/s	Max. RPM	Segment in mm: Number / Width / Height	Packing unit/pcs.	Cat. number
100 x 16 / 22,23	20	80 m/s	15300 rpm	16 / 8,5 / 5,5	1	330621
115 x 22,23	20	80 m/s	13300 rpm	16 / 8,2 / 5,5	1	325377
125 x 22,23	23,5	80 m/s	12200 rpm	20 / 7,2 / 5,5	1	325378
180 x 22,23	30,5	80 m/s	8500 rpm	24 / 8 / 5,5	1	325379

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

