

Hazardous Chemical, NON-Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: PU15

Synonyms

Adheseal PU15 Blk 600mls Adheseal PU15 Concrete Grey 600mls Adheseal PU15 White 600mls Product Code PU15BL/SSG PU15CGR/SSG PU15WH/SSG

Recommended use: Adheseal PU-15 is a low modulus, single component, moisture curing polyurethane sealant. It is tough and durable with a long skin time and good chemical resistance.

Supplier: ABN:	Adheseal 16 010 441 013
Street Address:	26 Wolverhampton Street
	Stafford
	Queensland 4053
Telephone:	(07) 3356 0000
Facsimile:	(07) 3356 0005
Email:	sales@adheseal.com.au

Emergency Telephone number: (07) 3356 0000

2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.



Signal Word

Danger

Hazard Classifications

Sensitisation - Respiratory - Category 1A Sensitisation - Skin - Category 1A

Hazard Statements

H317 May cause an allergic skin reaction.H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Prevention Precautionary Statements

P102 Keep out of reach of children.
P103 Read label before use.
P261 Avoid breathing fume, gas, vapours or spray..
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective clothing, gloves, eye/face protection and suitable respirator.
P285 In case of inadequate ventilation wear respiratory protection.

Response Precautionary Statements

P101	If medical advice is needed, have product container or label at hand.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.

Product Name: PU15



P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a
	position comfortable for breathing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.
P363	Wash contaminated clothing before reuse.

Storage Precautionary Statement

Not allocated

Disposal Precautionary Statement

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

Poison Schedule: Not Applicable

DANGEROUS GOOD CLASSIFICATION

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

3. COMPOSITION INFORMATION		
CHEMICAL ENTITY	CAS NO	PROPORTION
Benzene, ethyl- Calcium oxide Distillates, petroleum, hydrotreated light Polyurethane Xylene Ingredients determined to be Non-Hazardous	100-41-4 1305-78-8 64742-47-8 1330-20-7	<2.5 % (w/w) <2.5 % (w/w) <2.5 % (w/w) 30-50 % (w/w) 2-5 % (w/w) Balance
		100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Consult doctor if symptoms persist. In case of unconsciousness, place patient stably in side position for transportation

Skin Contact: Immediately wash with water and soap and rinse thoroughly

Eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor

Ingestion: If swallowed, do not induce vomiting. Seek medical advice.

PPE for First Aiders: Wear gloves, apron, safety glasses, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically. Effects may be delayed. Treat symptomatically



5. FIRE FIGHTING MEASURES

Hazchem Code: Not applicable.

Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Non-combustible material.

Fire fighting further advice: Not applicable.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

LARGE SPILLS

Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of dust. Work up wind or increase ventilation. Cover with damp absorbent (inert material, sand or soil). Sweep or vacuum up, but avoid generating dust. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: Not applicable

7. HANDLING AND STORAGE

Handling: Avoid eye contact and skin contact. Avoid inhalation of dust.

Storage: store in dry and cool condition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits:

	T١	VA	ST	TEL	NOTICES
	ppm	mg/m3	ppm	mg/m3	
Calcium oxide	-	2	-	-	-
Ethyl benzene	100	434	125	543	-
Xylene	80	350	150	655	

As published by Safe Work Australia.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative



toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Avoid generating and inhaling dusts. Use with local exhaust ventilation or while wearing dust mask.

Personal Protection Equipment: GLOVES, APRON, SAFETY GLASSES, RESPIRATOR.

Personal protective equipment (PPE) must be suitable for the nature of the work and any hazard associated with the work as identified by the risk assessment conducted.

Wear gloves, apron, safety glasses, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of dust. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

	5
--	---

Solubility: Solubility in water: Specific Gravity: Flash Point (°C): Autoignition Temperature (°C): No data avaiable Insoluble ~1.17 >70 (ISO3679) >200

(Typical values only - consult specification sheet) N Av = Not available, N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: stable at room temperature

Conditions to avoid: Moisture & Heat

Incompatible materials: alcohols, amines, aqueous acids and alkali.

Hazardous decomposition products: No decomposition if used according to specifications



Hazardous reactions: Reacts with water forming carbon dioxide.Danger of receptacles bursting because of vapour overpressure.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material may be an irritant to mucous membranes and respiratory tract. A respiratory sensitiser. Can cause possible allergic reactions.

Skin contact: May be slightly irritant.No sensitizing effects known. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Eye contact: Light irritating effect Exposure to the dust may cause discomfort due to particulate nature. May cause physical irritation to the eyes.

Acute toxicity

Inhalation: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): LC50 > 5 mg/L

LC50 (Rat): 6350mg/lt

Skin contact: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg bw

LD50 (Rabbit): >2000 mg/m3 LD50 (Rabbit): 17800mg/lt

Ingestion: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg bw

LD50 (Rat): 8700mg/kg LD50 (Rat): 3500mg/kg

Corrosion/Irritancy: Eye: this material has been classified as not corrosive or irritating to eyes. Skin: this material has been classified as not corrosive or irritating to skin.

Sensitisation: Inhalation: this material has been classified as a Category 1A Hazard (respiratory sensitiser). Skin: this material has been classified as a Category 1A Hazard (skin sensitiser).

Aspiration hazard: This material has been classified as non-hazardous.

Specific target organ toxicity (single exposure): This material has been classified as non-hazardous.

Chronic Toxicity

Mutagenicity: This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): This material has been classified as non-hazardous.



Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: slightly hazardous for water.

Long-term aquatic hazard: This material has been classified as non-hazardous. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log K_{ow} < 4.

Ecotoxicity: Do not allow product to reach ground water, water course or sewage system.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Must be disposed of in an incinerator for hazardous waste according to official regulations

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

AIR TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances) The Stockholm Convention (Persistent Organic Pollutants) The Rotterdam Convention (Prior Informed Consent) Basel Convention (Hazardous Waste) International Convention for the Prevention of Pollution from Ships (MARPOL)

This material/constituent(s) is covered by the following requirements:

• All components of this product are listed on or exempt from the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Product Name: PU15

Version:



Reason for issue: Revised

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.